



SILVER 48



Pump A		
Pneumatic Motor instant volumetric reversal		
Ratio	48:1	
Pump Capacity per Double Stroke	cm ³	110
Stroke	mm	100
Max. Delivery	ltr/min	25,0
Max. Working Pressure Bar (PSI)		385 (5584)
Max. Air Inlet Pressure Bar (PSI)		8 (116)
Air Consumption:	ltr/min	600 -2650

Application

2K anti-corrosive coatings, Acrylics, Bitumens, Colourings, Detergent and degreasers, Emulsions, Emulsions, Enamels, Epoxy coatings, Fillers, Fixatives Flame retardants, Gavanized, Lacquers, Latex, Natural coatings, One and 2K coatings, Polyurethane coatings, Primers, Product for tanneries, Protective coatings, Removers, Silicate, Textured paints, Undercoat paints, Water and solvent-based coatings, Water paints

Pump B		
Pneumatic Motor instant volumetric reversal		
Ratio	30:1	
Pump Capacity per Double Stroke	cm ³	64
Stroke	mm	100
Max. Delivery	ltr/min	7,0
Max. Working Pressure Bar (PSI)		240 (3480)
Max. Air Inlet Pressure Bar (PSI)		8 (116)
Air Consumption:	ltr/min	250-750

Application's fields:

Anti-corrosion painting • Epoxy coating • Paintwork • Protective treatments • Structural steelwork • Waterproofing Application

BIMIX Spray Gun



BIMIX is a two components airless spray gun with external mixing for an easy maintenance. **BIMIX** spray gun is also available with extension (length on choice) for spraying in those working places not easy to reach with a common spray gun.

Performances:

- Outside mixing for an easy maintenance
- Light and handy - built for a long work without effort
- Constant jet without fluctuations
- Even coverage
- Speed work with perfect finishing
- Reduced Overspray
- High Transfer Speed



Features:

- All parts in contact with product are in stainless steel
- Max. working pressure: up to 400 bar
- Diffuser 11/16" or 7/8"
- Fittings and swivels in stainless steel 1/4" or 16x1,5
- Safety Lever



**Airless Spray Gun
external mixing**

